

Single Check Valves

Single check valves are used in fire protection systems to allow waterflow in one direction only. Typical applications are at connections between public water supplies and private fire service systems, at the discharge from fire pumps, at gravity tank connections and at fire service pumper connections.

Valves identified in the listing by a single asterisk (*) have side covers; valves identified by a double asterisk (**) have no removable covers; others have top covers. Clearance must be provided for side-cover valves to permit clapper removal. Valves without covers must be removed from the system for clapper replacement or repair. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Fig No. 5201-300-F, 5201-250-F, 5201-200-F, Fig No. 5905-300-G, 5905-250-G, 5905-200-G

Model No.	Description	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
Fig. 5201-300-F	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	300 (2070)	a
Fig. 5201-250-F	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	250 (1725)	a
Fig. 5201-200-F	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	200 (1380)	a
Fig No. 5905-300-G	Swing Check Valve, Grooved Ends	2, 2 1/2, 76.1 mm, 3, 4, 5, 6, 8, 10, 12	300 (2070)	a
Fig No. 5905-250-G	Swing Check Valve, Grooved Ends	2, 2 1/2, 76.1 mm, 3, 4, 5, 6, 8, 10, 12	250 (1725)	a
Fig No. 5905-200-G	Swing Check Valve, Grooved Ends	2, 2 1/2, 76.1 mm, 3, 4, 5, 6, 8, 10, 12	200 (1380)	a

Remarks:

a. Resilient Seat

Company Name:	Weilong Valve Co Ltd
Company Address:	210 Shuangyuan Rd, Chengyang, Qingdao, Shandong 266111, China
Company Website:	http://www.weilongvalve.com
New/Updated Product Listing:	No
Listing Country:	China
Certification Type:	FM Approved